

YELLOWTOP®

THE ULTIMATE DUAL-PURPOSE BATTERY



WARRANTY

- 12V PASSENGER VEHICLE / LIGHT TRUCK (NONCOMMERCIAL) — 36 MONTHS FREE REPLACEMENT
- D31A AND D31T — 24 MONTHS FREE REPLACEMENT
- COMMERCIAL APPLICATIONS (EXCEPT D31A AND D31T) — 12 MONTHS FREE REPLACEMENT
- SERIES STRING APPLICATIONS WITH APPROVED BATTERY MANAGEMENT SYSTEM — 12 MONTHS FREE REPLACEMENT
- SERIES STRING APPLICATIONS WITHOUT APPROVED BATTERY MANAGEMENT SYSTEM — 1 MONTH FREE REPLACEMENT

PUREFLOW

MODEL #	VOLTAGE	COLD CRANKING AMPS @ 0°F	CRANKING AMPS @ 32°F	RESERVE CAPACITY	CAPACITY (C/20 RATE)	INTERNAL RESISTANCE	DIMENSIONS (MM)			WEIGHT	POST TYPE	GROUP TYPE GROUP SIZE	WARRANTY
							LENGTH	WIDTH	HEIGHT				
						OHMS				LBS			
H6	12V	800	928	140	72 Ah	0.003	278	175	190	54	DIN Post	H6	3-Year Free Replacement
H7*	12V	880	1000	154	80 Ah	0.003	315	175	190	60.5	DIN Post	H7	3-Year Free Replacement

SPIRALCELL

MODEL #	VOLTAGE	COLD CRANKING AMPS @ 0°F	CRANKING AMPS @ 32°F	RESERVE CAPACITY	CAPACITY (C/20 RATE)	INTERNAL RESISTANCE (OHMS)	DIMENSIONS			WEIGHT (LBS)	POST TYPE	GROUP/TYPE #
							LENGTH	WIDTH	HEIGHT			
D34/78	12V	750	870	120	55	.0028	10 1/16"	6 15/16"	7 7/8"	43.5	DUAL SAE/GM	34/78
D75/25	12V	620	770	100	48	.0030	9 3/8"	6 13/16"	7 3/4"	37.8	DUAL SAE/GM	75/25
D34	12V	750	870	120	55	.0028	10 1/16"	6 7/8"	7 7/8"	42.9	SAE POST	34
D35	12V	620	770	100	48	.0030	9 3/8"	6 3/4"	7 11/16"	36.4	SAE POST	35
D51	12V	450	575	66	38	.0046	9 5/16"	5 1/16"	8 15/16"	26	SAE POST	51
D51R	12V	450	575	66	38	.0046	9 5/16"	5 1/16"	8 15/16"	26	SAE POST	51R
DS46B24R	12V	450	575	66	38	.0046	9 5/16"	5 1/16"	8 15/16"	26	THIN POST T1	S46B24R
D31T	12V	900	1125	155	75	.0025	12 13/16"	6 9/16"	9 3/8"	59.8	3/8" Stainless Stud	31T
D31A	12V	900	1125	155	75	.0025	12 13/16"	6 9/16"	9 3/8"	59.8	SAE POST	31A
D27F	12V	830	1025	140	66	.0025	12 3/16"	6 13/16"	8 3/4"	53.2	SAE POST	27F

* Estimated availability, spring 2019

REDTOP®

THE ULTIMATE STARTING BATTERY

WARRANTY

- 6V AND 12V PASSENGER VEHICLE / LIGHT TRUCK (NONCOMMERCIAL) — 36 MONTHS FREE REPLACEMENT
- COMMERCIAL — 12 MONTHS FREE REPLACEMENT
- DEEP CYCLE APPLICATIONS / CAR AUDIO — NOT COVERED

MODEL #	VOLTAGE	COLD CRANKING AMPS @ 0°F	CRANKING AMPS @ 32°F	RESERVE CAPACITY	CAPACITY (C/20 RATE)	INTERNAL RESISTANCE (OHMS)	DIMENSIONS			WEIGHT (LBS)	POST TYPE	GROUP/TYPE #
							LENGTH	WIDTH	HEIGHT			
34/78	12V	800	1000	100	50	.0030	10 1/16"	6 15/16"	7 7/8"	38.8	DUAL SAE/GM	34/78
75/25	12V	720	910	90	44	.0030	9 3/8"	6 13/16"	7 3/4"	33.1	DUAL SAE/GM	75/25
25	12V	720	910	90	44	.0030	9 3/8"	6 3/4"	7 11/16"	31.7	SAE POST	25
34	12V	800	1000	100	50	.0030	10 1/16"	6 7/8"	7 7/8"	37.9	SAE POST	34
34R	12V	800	1000	100	50	.0030	10 1/16"	6 7/8"	7 7/8"	37.9	SAE POST	34R
35	12V	720	910	90	44	.0030	9 3/8"	6 3/4"	7 11/16"	31.7	SAE POST	35
78	12V	800	1000	100	50	.0030	10 1/16"	7 5/16"	7 1/4"	39.5	Side Terminal	78
6V	6V	800	1000	100	50	.0019	10 1/16"	3 5/8"	8 1/8"	18.5	SAE POST	N/A

BLUETOP®

THE ULTIMATE MARINE & RV BATTERY

WARRANTY

- CONSUMER APPLICATIONS — 24 MONTHS FREE REPLACEMENT
- COMMERCIAL APPLICATION — 12 MONTHS FREE REPLACEMENT
- SERIES STRING APPLICATIONS WITH APPROVED BATTERY MANAGEMENT SYSTEM — 12 MONTHS FREE REPLACEMENT
- SERIES STRING APPLICATIONS WITHOUT APPROVED BATTERY MANAGEMENT SYSTEM — 1 MONTH FREE REPLACEMENT
- USE OF 34M IN DEEP CYCLE / CAR AUDIO — NOT COVERED

MODEL #	VOLTAGE	COLD CRANKING AMPS @ 0°F	CRANKING AMPS @ 32°F	RESERVE CAPACITY	CAPACITY (C/20 RATE)	INTERNAL RESISTANCE (OHMS)	DIMENSIONS			WEIGHT (LBS)	POST TYPE	GROUP/TYPE #
							LENGTH	WIDTH	HEIGHT			
D27M	12V	800	1000	140	66	.0025	12 3/16"	6 13/16"	8 3/4"	53.8	DUAL SAE 5/16" Stainless Stud	27
34M*	12V	800	1000	100	50	.0030	10 1/16"	6 7/8"	7 15/16"	38.4	DUAL SAE 5/16" Stainless Stud	34
D34M*	12V	750	870	120	55	.0028	10 1/16"	6 7/8"	7 15/16"	43.5	DUAL SAE 5/16" Stainless Stud	34
D31M**	12V	900	1125	155	75	.0025	12 13/16"	6 9/16"	9 3/8"	59.8	DUAL SAE 5/16" Stainless Stud	31

*34M AND D34M MODELS FIT GROUP SIZE 24 MARINE BOXES AND TRAYS **D31M MODEL FITS GROUP 27 MARINE BOXES AND TRAYS